

ROLA MATERIAL FILTRANT

Poly 80-500

APLICATII

- Filtrare primara pentru sistemele de ventilatie si aer conditionat

AVANTAJE

- Cadere presiune initiala mica
- Rezistenta mecanica
- Densitate progresiva



CARACTERISTICI GENERALE

- Eficienta conform ISO 16890:2016
- Mediu filtrant : Sintetic
- Cadere de presiune finala: 250Pa
- Temperatura maxima de lucru : 110 °C
- Umiditate maxima : 100% RH

Cod Produs	Descriere	Latime A (mm)	Lungime B (m)	Grosime C (mm)±3	Suprafata Totala (m ²)	Debit aer (m ³ /h)	Cadere de presiune P (Pa)
G2 ISO COARSE 40% ISO16890 SR EN 779/2012							
RG200157	POLY 100	2000	20	6	40	5400	20
G3 ISO COARSE 50% ISO16890 SR EN 779/2012							
RG300441	POLY150	2000	20	15	40	5400	22
RG300031	POLY80M1	2000	40	10	80	5400	19
RG300032	POLY80	2000	20	10	40	5400	19
RG300614	POLY200	2000	20	20	40	5400	27
G4 ISO COARSE 60% ISO16890 SR EN 779/2012							
RG400234	POLY290	2000	20	20	40	5400	35
RG400265	POLY350	2000	20	20	40	5400	40
RG400278	POLY500	2000	20	22	40	5400	76

